

Focus PAS 10

PRODUCT DESCRIPTION

Focus PAS 10 and **Focus PAS 15** are light-colored, low odor, high molecular weight sulfurized additives. They are extreme pressure and lubricity additives, imparting outstanding metal removal while giving excellent lubrication properties to the finished fluid. They are inactive to copper @ 100 °C. They contain no chlorine or phosphorous.

APPLICATIONS

Focus PAS 10 and **Focus PAS 15** totally replace chlorinated paraffins and chlorinated fatty acids in industrial cutting oils and soluble oils. They are designed for machining stainless steel and other hard metals.

Focus PAS 10 and **Focus PAS 15** are non-staining per the ASTM D-130 copper strip test. Both products are soluble in paraffinic and naphthenic base oils.

TYPICAL PROPERTIES

Feature	Data	
	Focus PAS 10	Focus PAS 15
Appearance	Light amber	Light amber
Specific gravity @ 25 °C	0.97	1.01
Weight per gallon	8.08	8.41
Flash point (°C), COC	340	315
Viscosity @ 40 °C (cSt)	270	860
Viscosity @ 100 °C (cSt)	34	83
Viscosity index	172	180
Sulfur content (% wt.)	10	15
Copper strip test, 10% wt. in oil, ASTM D-130, 3 hr @ 100 °C	1b	1b
Four ball EP weld (kg), 5%, HVI 100 SUS oil	400	500

PACKAGING

Packaging	Description	Net Weight
Drums	55 gallon non-returnable	435 lbs.

REGISTRATION

USA	TSCA
Canada	DSL

HANDLING, SAFETY, HEALTH AND ENVIRONMENT

See safety data sheet

NOTE: All statements, information, and data that are given in this bulletin are believed to be accurate and reliable, but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied on our part. Because we have no control over the matter in which our products may be used, we cannot be responsible for the results in customers' processes.